

Repair & Painting Work At Buddha Smriti Park, Patna

S.No	BCD SOR 2016	Description Of Work	Unit	Q'ty	Rate	Amount in Rs.
1	13.74	Removing white or colour wash by scrapping and sand paper in and preparing the surface smooth including necessary repair scratches etc. complete	Sqm	279.28	4.6	Rs. 1,284.70
2	13.80 A.1	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	279.28	77.4	Rs. 21,616.43
3	13.48.1	Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers				
		Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of special primer applied @ 0.75 ltr /10 sqm..	Sqm	1695.79	81.4	Rs. 138,037.39
4	13.46A.1	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade				
		New work (Two or more coat applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior	Sqm	279.21	83.6	Rs. 23,341.96
5	13.82.3	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade:				
		Old steel work (one or more coats)	Sqm	632.06	40.7	Rs. 25,725.01
6	13.101.2	French spirit polishing:				
		One or more coats on old work.	Sqm	1036.51	71.00	Rs. 73,592.38
7	13.79.2	Finishing walls with water proofing cement paint of approved brand and manufacture and of required shade to give an even	Sqm	2174.81	42.8	Rs. 93,081.77
8	13.70.2	White washing with lime to give an ever shade				
		Old work (two or more coats)	Sqm	7538.87	6.9	52018.22

9	21.3.2	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item) With float glass panes of 5.50 mm thickness	Sqm	19.86	998.4	Rs. 19,828.22
10	25.2	Providing and fixing double scaffolding system (cup lock type) on the exterior side of building/structure, upto 25 metre height, above ground level, including additional rows of scaffolding in stepped manner as per requirement of site, made with 40mm dia M.S. tube, placed 1.5 metre centre to centre, horizontal & vertical tubes joint with cup & lock system with M.S. Tubes, M.S. tube chalis, M.S. clamps and staircase system in the scaffolding for working platform etc.	Sqm	232.77	126.2	Rs. 29,376.18
11	12.60A	with 12 mm thick plain/or with design ceiling tiles of BWP type phenol formaldehyde synthetic resin bonded pressed particle board conforming to IS :3087 finished with a coat of aluminum primer on both sides & edges and two coats of synthetic enamel paint of approved quality on exposed face fixed to a grid made out of anodized aluminum (with 15 micron anodic coating) T-sections 35x15x1.5 mm size main runners and cross runners 23.5x19x1.5 mm fixed to main runners placed 600 mm centre to centre both ways so as to form a grid of 600 mm square. The frame work shall be suspended from ceiling by level adjusting hangers of 6 mm dia M.S. rod fixed to roof slab ny means of	Sqm	27.03	591.1	Rs. 15,974.86
				TOTAL		Rs. 493,877.12